

## SITE INVESTIGATION REPORT FORM

FOR A TYPE 4.02 TO 4.23 GENERAL PERMIT FOR ON-SITE WASTEWATER TREATMENT FACILITY

## **O**VERVIEW

The purpose of this form is to summarize the results of a site investigation conducted under A.A.C. R18-9-A310. This form must be submitted in conjunction with a "Notice of Intent to Discharge for an On-site Wastewater Treatment Facility" in accordance with Arizona Administrative Code (A.A.C.) R18-9-A309(B)(1). The report includes the following information:

- A) Results from any soil evaluation, percolation test, or seepage pit performance test;
- B) Any surface limiting condition identified in R18-9-A310(C)(2); and
- C) Any subsurface limiting condition identified in R18-9-A310(D)(2).

GE	NERAL INFORMATIO	N						
1	Project Identifica	tion (if known)						
	Project Name							
2	Person Authorizi	ng this Site Investig	gation purs	uant to A.A.C.	R18-9-A310			
	Name				Phone			
					Firm Name			
					City		State	
	Zip	E-	Mail _					
3	Site Information							
	County				City			
	Parcel Number				Lot Number			
	Township	Range _		Section	Longitude			
								" W
		· · · · · · · · · · · · · · · · · · ·	S 4 THROU	IGH 12 AND AP	PLICABLE ATTACH	MENTS ARE TO	BE COMPL	ETED BY
	E SITE INVESTIGA	, , , , , , , , , , , , , , , , , , ,						
4		terization Method 0-95 used? Yes		R18-9-A310(C	()(1)]			
	A) ASIM D58/9	7-95 used? \( \text{Y es}	∐ No					
5		g Conditions [A.A						
					he following surface line of the on-site wastewa			
	· /				in R18-9-A312(C); $\Box$			□No
	,				velling or other improv			
					N PERFORMING THI			
					ne on-site wastewater t s, please describe in A			rsely affect
					e flood insurance rate			property on
	which the on-	site wastewater treat	ment facilit	y will be installe	ed; Yes No			1 - 3
	the FEMA Flo	ood Insurance Map N	Number or C	Other Source	. :	1	)	C:1:4
		ir the function of soi			e intended location of t	the on-site waste	water treatm	ent facility
					ite wastewater treatmen	nt facility \[ \]	res No.	
	IF THE ANSWER	IS YES OR INDETI	ERMINATE	TO ANY OF TH	E ABOVE SURFACE L	IMITING COND	ITIONS, PLEA	ASE SHOW

LOCATION AND NOTE THE ASSOCIATED LIMITING CONDITION TYPE ON SITE INVESTIGATION MAP (ITEM 8).

Su	bsurface Characterization Method [A.A.C. R18-9-A310(D)]
Me	thod used to perform subsurface characterization per A.A.C. R18-9-A310(D)(1) and (3)
	ASTM D5921 used? Yes No (if Yes, please enclose Attachment 1)
B)	Percolation test method used? Yes No (if Yes, please enclose Attachment 2)
	Seepage performance test method used?
	bsurface Limiting Conditions [A.A.C. R18-9-A310(D)(2)]
	e investigator shall determine whether any of the following limiting conditions exist in the primary and reserve areas of the
on-	site wastewater treatment facility to a depth of at least 12 feet below land surface or to an impervious soil or rock layer if
	countered at a shallower depth:  The soil absorption rate determined under A.A.C. R18-9-A312(D)(2) is:
A)	1. More than 1.20 gallons per day per square foot? $\square$ Yes $\square$ No
	2. Less than 0.20 gallons per day per square foot? Yes No
	3. A site-specific soil absorption rate (SAR) is required per A.A.C. R18-9-A312(D)(2)(b)?  Yes No
B)	The vertical separation distance from the bottom of the lowest point of the disposal works to the seasonal high water table
~`	is less than the minimum vertical separation specified in A.A.C. R18-9-A312(E)(1)?
C)	Does seasonal saturation occur within surface soils that could affect the performance of the on-site wastewater treatment
	facility? Yes No If Yes, describe evidence:
D)	Do any of the following subsurface limiting conditions that may cause or contribute to surfacing of wastewater occur within 12 feet of the land surface:
	1. An impervious soil or rock layer?  Yes No
	2. A zone of saturation that substantially limits downward percolation from the disposal works? Yes No
	3. Soil with more than 50 percent rock fragments? Yes No
E)	Do any of the following subsurface limiting conditions that may promote accelerated downward movement of
	insufficiently treated wastewater occur within 12 feet of the land surface:
	1. Fractures or joints in rock that are open, continuous, or interconnected? Yes No
	2. Karst voids or channels?  \[ \text{Yes} \] No
F)	3. Highly permeable materials such as deposits of cobbles or boulders?  Yes No  Does a subsurface condition exist that may convey wastewater to a Water of the State and cause or contribute to an
rj	exceedance of a water quality standard established in 18 A.A.C. 11, Articles 1 and 4? Yes No
G)	Depth to groundwater below land surface feet.
	Please check below the method used.
	☐ Trench or boring, ☐ Subdivision report,
	☐ Published groundwater data, ☐ Relevant well data.
IF	THE ANSWER IS YES TO ANY OF THE ABOVE SUBSURFACE LIMITING CONDITIONS, PLEASE SHOW LOCATION AND NOTE THE
	SOCIATED LIMITING CONDITION TYPE ON SITE INVESTIGATION MAP (ITEM 8).

N Other easement

## SITE INVESTIGATION REPORT FORM Site Investigation Map (Show locations of limiting conditions, features and improvements) 8 The Site Investigation Map may be shown below on the Grid **OR** on an Attachment. The Map shall show: A) The property boundaries, a North arrow, soil test sites, and the positions of limiting conditions noted in Items 5 and 7; B) All observed conditions or features specified in A.A.C. R18-9-A312(C) are shown with the planned separation distance shown in feet (please circle below the "N" for each potential limiting condition that is Not Observed or Not Determined and THEREFORE, is not shown in this Site Investigation Map); N Drinking water intake from a surface water source N Planned building N Existing building N Water main or branch water line N Domestic service water line N Water supply well N Wall or planned wall over 2 feet high N Perennial or intermittent stream N Lake, reservoir, or canal N Planned cut bank over 2 feet deep


N Pond or other water feature N Driveway, vehicle path, or parking area, existing or planned N Wash, or drainage easement N Swimming pool, existing or planned

N Property line or survey corner

N Boundary of 100-year flood hazard zone N Storage Area - Equipment or material storage area, or other storage

AND C) Any other condition or feature observed during the site investigation which may affect on-site system design which is located within the Site Investigation Area (defined as the planned excavation boundaries for the treatment works, primary disposal area and reserve disposal area plus the surrounding area out to 100 feet ) including: (1) land surface contours at appropriate intervals when the elevations across this Area differ by more than 5 feet, and (2) any other factor is observed that may affect system design regardless of property ownership (Use an Attachment if it cannot be depicted on the below Grid).

N Earth fissure



9	Investigator Information		
	Name	Phone	
	Title	Eima Mana	
			State
	Mailing Address Zip E-Mail		
10	Investigator Qualification Information [A.A.C. R18090A3] information)	10(H)] (Must check app	plicable boxes and provide related
	A) Arizona-registered professional engineer Certification	Number:	Expiration Date:
	B) Arizona-registered professional geologist Certificatio		Expiration Date:
	C) Arizona-registered sanitarian Registration Number:		Expiration Date:
	D) A certificate of training from a course recognized by	ADEQ	
	Course Name:		Completion Date:
	E) Qualifies under another category designated in writing	g by ADEQ. Specify Ca	tegory and Approval Date.
	Qualification Category:		Approval Date:
11	Investigator Certification		
	I have inspected the property identified in Item 3, Site Informa performed this site investigation in accordance with R18-9-A3 knowledge. This Site Investigation report is intended to be sult the following attachments.	10 and have completed 1	Items 3 through 11 to the best of my
	# Attachment Description		Attached?
			Yes, total of pages.
			Yes, total of pages.
			Yes, total of pages.
			Yes, total of pages.
	Investigator Name (Printed):	Date of	Investigation:
	Investigator Signature:	Date Si	gned:
12	Affidavit of Person Authorizing This Site Investigatio		
	I certify that I am the Person authorizing the work certified in		rformed in fulfillment of
	A.A.C. R18-9-A310, effective November 12, 2005, for Parcel My interest in this Site Investigation as it relates to the installa check all applicable boxes and provide a description, if specific I am the Owner of the property described above.	tion of an on-site wastev	vater treatment facility is that (please
	☐ I am the Representative of the Owner, such as a person pro	eparing a submittal purs	uant A.A.C. R18-9-A309(B).
	Other. Please describe:		
	Signature		ate
	SPACE FOR REVIEWING AGENCY USE (EACH AGENCY T		

**Comments:** 

## ATTACHMENT 1 – ASTM 5921 METHOD FOR SUBSURFACE SOIL CHARACTERIZATION

Address of Facility Tested by Date Tested		Depth to Groundwater Parcel Number	PLEASE REPORT IN ITEM 7.G	
Test	Test	Test	Test	

Test Hole #	Depth Interval Below Land Surface (Inches)	Texture	Structure	Rock Fragments %	Mottles %	Boundary	Dry Consistency	Moist Consistency	SAR

GWS FORM 423 (REV. MAR 2006)

ATTACHMENT 1 - PAGE 1 of 2

STRUCTURE

TEXTURE

	STRUCTURE						
Loamy Sand – (LS)	<u>GRADE</u>						
Sandy Loam – (SL)	Structureless	(0)	No aggregation				
Silt Loam – (SiL)	Weak	(1)	Barely observable				
Loam – (L)	Moderate	(2)	Distinct peds				
	Strong	(3)	Durable peds	Angular,			
Sandy Clay Loam – (SCL)				Subangular,			
Silty Clay Loam – (SiCL)	SIZE		Granular, Platy	Blocky	Prismatic, Columnar		
Clay Loam – (CL)	Very Fine	(VF)	<1 mm	<5 mm	<10 mm		
Sandy Clay – (SC)	Fine	(F)	1-2	5-10	10-20		
Silty Clay – (SiC)	Medium	(M)	2-5	10-20	20-50		
Clay - (C)	Coarse	(C)	5-10	20-50	50-100		
	Very Coarse	(VC)	>10	>50	>100		
SAND SIZES							
	SHAPE						
Coarse – (Co)		(DL)	Elet plata lika				
Medium – (M)	Platy	(PL)	Flat, plate-like Taller than wide				
Fine – (F)	Prismatic	(PR)					
Very Fine – (VF)	Columnar	(CPR)	Rounded tops				
	Blocky	(BK)	Cubical				
	Angular	(ABK)	Sharp edges				
	Subangular	(SBK)	Rounded edges				
	Granular	(GR)	Spherical				
	No Structure	(00)	6 1 4 4				
	Single Grain	(SG)	Sandy texture Finer textures				
	Massive	(M)	Finer textures				
					CONSIS	STENCY	
DOCK ED A CMEN							SAR (gnd/ft <sup>2</sup> )
ROCK FRAGMEN	ΓS	MOTTLES	BOUNDARY		DRY	MOIST	SAR (gpd/ft <sup>2</sup> )
ROUNDED,	TS TYPE OF ROCK	MOTTLES  QUANTITY	BOUNDARY DISTINCTNESS				
ROUNDED, SUBROUNDED	ΓS	MOTTLES  QUANTITY Few (F) -<2%	BOUNDARY	2 cm	DRY L = Loose	MOIST L = Loose	SAR (gpd/ft <sup>2</sup> ) See Arizona
ROUNDED, SUBROUNDED ANGULAR,	TS TYPE OF ROCK	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20%	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than	2 cm	DRY	MOIST	See Arizona
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND)	MOTTLES  QUANTITY Few (F) -<2%	BOUNDARY DISTINCTNESS	2 cm	DRY L = Loose S = Soft	MOIST  L = Loose  VFR = Very Friable	
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST)	MOTTLES  QUANTITY Few (F) -< 2% Common (C) - 2-20% Many (M) -> 20%	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm		DRY  L = Loose  S = Soft  SH = Slightly Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable	See Arizona Administrative
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cr	n	DRY L = Loose S = Soft	MOIST  L = Loose  VFR = Very Friable	See Arizona
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)	MOTTLES  QUANTITY Few (F) -< 2% Common (C) - 2-20% Many (M) -> 20%	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm	n	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm	See Arizona Administrative Code(A.A.C.)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm Coarse – (CGR) 20-75 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST) TERMS OF	MOTTLES  QUANTITY Few (F) -< 2% Common (C) - 2-20% Many (M) - > 20%  SIZE Fine (1) - < 5 mm	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cr	n	DRY  L = Loose  S = Soft  SH = Slightly Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable	See Arizona Administrative
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)  TERMS OF SOIL/ROCK	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) - >20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) - >15 mm	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than	n	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm Coarse – (CGR) 20-75 mm Pebbles – (PB) 2-75 mm Fine – (FPB) 2-5 mm Medium – (MPB) 5-20 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST) TERMS OF	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than	m n 15 cm	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm	See Arizona Administrative Code(A.A.C.)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm Coarse – (CGR) 20-75 mm Pebbles – (PB) 2-75 mm Fine – (FPB) 2-5 mm Medium – (MPB) 5-20 mm Coarse – (CPB) 20-75 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)  TERMS OF SOIL/ROCK	MOTTLES  QUANTITY Few (F) -< 2% Common (C) - 2-20% Many (M) -> 20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) -> 15 mm  CONTRAST Faint - (F)	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than	m n 15 cm	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium - (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm	TYPE OF ROCK Basalt - (BAS) Cinders - (CIND) Sandstone - (SST) Limestone - (LST)  TERMS OF SOIL/ROCK Cemented - (CEM) Ice or Frozen - (ICE)	MOTTLES  QUANTITY Few (F) -< 2% Common (C) - 2-20% Many (M) -> 20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) -> 15 mm  CONTRAST Faint - (F) Distinct - (D)	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane w	m n 15 cm	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium- (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm Stones - (SPB) 2-50 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)  TERMS OF SOIL/ROCK Cemented – (CEM) Ice or Frozen – (ICE) Weathered – (WEA)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) - >20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) - >15 mm  CONTRAST Faint - (F)	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than	m n 15 cm	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium - (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm	TYPE OF ROCK Basalt - (BAS) Cinders - (CIND) Sandstone - (SST) Limestone - (LST)  TERMS OF SOIL/ROCK Cemented - (CEM) Ice or Frozen - (ICE) Weathered - (WEA) Unweathered -	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane wirregularities	n 15 cm rith few or no	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm Coarse – (CGR) 20-75 mm Pebbles – (PB) 2-75 mm Fine – (FPB) 2-5 mm Medium – (MPB) 5-20 mm Coarse – (CPB) 20-75 mm Cobbles – (CB) 75-250 mm Stones – (S) 250-600 mm Boulders – (B) ≥600 mm	TYPE OF ROCK Basalt - (BAS) Cinders - (CIND) Sandstone - (SST) Limestone - (LST)  TERMS OF SOIL/ROCK Cemented - (CEM) Ice or Frozen - (ICE) Weathered - (WEA) Unweathered (UNWEA)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane w	n 15 cm rith few or no	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm Coarse – (CGR) 20-75 mm Pebbles – (PB) 2-75 mm Fine – (FPB) 2-5 mm Medium – (MPB) 5-20 mm Coarse – (CPB) 20-75 mm Cobbles – (CB) 75-250 mm Stones – (CB) 75-250 mm Stones – (S) 250-600 mm Boulders – (B) ≥600 mm	TYPE OF ROCK Basalt - (BAS) Cinders - (CIND) Sandstone - (SST) Limestone - (LST)  TERMS OF SOIL/ROCK Cemented - (CEM) Ice or Frozen - (ICE) Weathered - (WEA) Unweathered -	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report Soil Color in	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than and Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than and TOPOGRAPHY Smooth (S) – A plane we irregularities  Wavy (W) – Waves with	n 15 cm rith few or no der than deep	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel – (GR) 2-75 mm Fine – (FGR) 2-5 mm Medium– (MGR) 5-20 mm Coarse – (CGR) 20-75 mm Pebbles – (PB) 2-75 mm Fine – (FPB) 2-5 mm Medium – (MPB) 5-20 mm Coarse – (CPB) 20-75 mm Cobbles – (CB) 75-250 mm Stones – (S) 250-600 mm Boulders – (B) ≥600 mm	TYPE OF ROCK Basalt - (BAS) Cinders - (CIND) Sandstone - (SST) Limestone - (LST)  TERMS OF SOIL/ROCK Cemented - (CEM) Ice or Frozen - (ICE) Weathered - (WEA) Unweathered (UNWEA)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report Soil Color in "Comments"	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane wirregularities	n 15 cm rith few or no der than deep	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium- (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobbles - (CB) 75-250 mm Stones - (S) 250-600 mm Boulders - (B) ≥600 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)  TERMS OF SOIL/ROCK Cemented – (CEM) Ice or Frozen – (ICE) Weathered – (WEA) Unweathered – . (UNWEA) Fractured – (FRA) Decomposed – (DEC)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report Soil Color in	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cr Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane w irregularities  Wavy (W) – Waves wid Irregular (I) – Waves de	n 15 cm with few or no eler than deep	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium- (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm Stones - (S) 250-600 mm Stones - (S) 250-600 mm FLAT Channers - (CH) 2-150 mm Flagstones - (FL) 150-380 mm	TYPE OF ROCK Basalt - (BAS) Cinders - (CIND) Sandstone - (SST) Limestone - (LST)  TERMS OF SOIL/ROCK Cemented - (CEM) Ice or Frozen - (ICE) Weathered - (WEA) Unweathered - (UNWEA) Fractured - (FRA)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report Soil Color in "Comments" when Mottles are	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than and Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than and TOPOGRAPHY Smooth (S) – A plane we irregularities  Wavy (W) – Waves with	n 15 cm with few or no eler than deep	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium- (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm Cobbles - (CPB) 20-75 mm Stones - (S) 250-600 mm Stones - (S) 250-600 mm FLAT Channers - (CH) 2-150 mm Flagstones - (FL) 150-380 mm Stones - (ST) 380-600 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)  TERMS OF SOIL/ROCK Cemented – (CEM) Ice or Frozen – (ICE) Weathered – (WEA) Unweathered – . (UNWEA) Fractured – (FRA) Decomposed – (DEC)	MOTTLES  QUANTITY Few (F) -< 2% Common (C) - 2-20% Many (M) -> 20%  SIZE Fine (1) - < 5 mm Medium (2) - 5 -15 mm Coarse (3) -> 15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report Soil Color in "Comments" when Mottles are Common or	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cm Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane wirregularities  Wavy (W) – Waves wid Irregular (I) – Waves de Broken (B) – discontinu	n 15 cm with few or no eler than deep	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)
ROUNDED, SUBROUNDED ANGULAR, IRREGULAR Gravel - (GR) 2-75 mm Fine - (FGR) 2-5 mm Medium- (MGR) 5-20 mm Coarse - (CGR) 20-75 mm Pebbles - (PB) 2-75 mm Fine - (FPB) 2-5 mm Medium - (MPB) 5-20 mm Coarse - (CPB) 20-75 mm Cobles - (CPB) 20-75 mm Cobles - (CPB) 20-75 mm Stones - (S) 250-600 mm Stones - (S) 250-600 mm FLAT Channers - (CH) 2-150 mm Flagstones - (FL) 150-380 mm Stones - (ST) 380-600 mm	TYPE OF ROCK Basalt – (BAS) Cinders – (CIND) Sandstone – (SST) Limestone – (LST)  TERMS OF SOIL/ROCK Cemented – (CEM) Ice or Frozen – (ICE) Weathered – (WEA) Unweathered – . (UNWEA) Fractured – (FRA) Decomposed – (DEC)	MOTTLES  QUANTITY Few (F) -<2% Common (C) - 2-20% Many (M) ->20%  SIZE Fine (1) - <5 mm Medium (2) - 5 -15 mm Coarse (3) ->15 mm  CONTRAST Faint - (F) Distinct - (D) Prominent - (P)  NOTE: Report Soil Color in "Comments" when Mottles are	BOUNDARY  DISTINCTNESS Abrupt (A) – Less than Clear (C) – 2 to 5 cm Gradual (G) – 5 to 15 cr Diffuse (D) – More than  TOPOGRAPHY Smooth (S) – A plane w irregularities  Wavy (W) – Waves wid Irregular (I) – Waves de	n 15 cm with few or no eler than deep	DRY  L = Loose S = Soft SH = Slightly Hard MH = Moderately Hard VH = Very Hard H = Hard R = Rigid	MOIST  L = Loose  VFR = Very Friable  FR = Friable  FI = Firm  VFI = Very Firm  EFI = Extremely Firm  SR = Slightly Rigid  R = Rigid	See Arizona Administrative Code(A.A.C.) R18-9-A312(D)

GWS FORM 423 (REV. MAR 2006)
ATTACHMENT 1 PAGE 2 OF 2

ATTACE	IMENT 2 -	- PERCOLATI	ON TEST DA	TASH	EET					
	ace at the to	op of the Test Hove Soil			ne): 1 Surface					
Other	(describe)									
	Number/L from Test	ocation <b>Hole:</b>				Date Teste	ed			
1	(inches)	Soil Texture	Soil Struct	ture	Soil Consis	stence	Mot	tles	% Ro	ck
D 41 C1		- 4 1- 1- 1- 1- 1- 1-		\ : <b>1</b> :	-4-1-1	:1				
-		est hole below la r (feet bls): <b>PLE</b>	•	*		inches.				
		st hole				ole	inches.			
Test Hole	cross section	on					•			
		inches in	diameter [	Squ	ıare, iı	nch sides				
Test Hole Run #	Presoakir Start D		rt Time	-	End Time	Elapsed	l Time		Initial Dept	th
Kull #	(M:D:		:M::S)		(H:M::S)	Elapset (mi			(inches)	ııı
T4 H - 1 -	D	т. т.	•			•		•		
Run	Percolation Start	End	Elapsed		Measured	Percolation	on (	$T_i + T_{i+1})/2$	$P_{i+1} - P_i$	ΔΡ/ ΔΤ
#	Time	Time	Time, T <sub>i</sub>	1	Water Drop	Rate, Pi	i	ΔT(min)	ΔΡ	
	(H:M::S	(H:M::S)	(min)		(inches)	(min/in.		[/A	N/A	N/A
Stabilize	d Percolation	on Rate (from G	raph)		inches				Professional S	Seal
Person v	vho perform	ned the test:								
Name:	no p <b>e</b> rrorn									
Compan	y:									
Company Address: Phone			Fax							

GWS FORM 423 (REV. MAR 2006)

ATTACH	IMENT 3 – SE	EEPAGE PIT T	TEST DATAS	НЕЕТ		
Test Hole Date Rep Prepared				nches) elow PLEASE REPORT IN ITEM 7.G		
Soil data f  Depth	from test hole: (feet)			Soil	Lithology	
Presoaking	~					
Run #	Start Date (M:D:Y)	Start 7 (H:M		End Time (H:M::S)	Elapsed Time (min)	Initial Water Surface Depth Below Ground Surface (inches)
Total gallo	ons of water ad	ded to the Test	Hole for presoa	ak	gallons.	
Seepage P Run #	Start Time (H:M::S)	End Time (H:M::S)	Elapsed Time, T <sub>i</sub> (min)	Measured Water Drop (inches)	Percolation Rate, P <sub>i</sub> (min/in.)	$(P_{i+1} - P_i)/P_i * 100\%$
		Rate (from Grap	h)	inches		Professional Seal
Name:	ho performed t	the test:				
Company Address:						
Phone			Fax			
Email						

GWS FORM 423 (REV. MAR 2006)

ATTACHMENT 4 – OTHER INFORMATION		
Other information pertinent to this Site Investigation Report: Ple	ase specify the Report Item and/or Attachn	nent.
	Continued on pages	through
repared by:		
Date Prepared:		

GWS FORM 423 (REV. MAR 2006)